



1N6-G



DIODE - POWER AMPLIFIER PENTODE

Filament	Coated	
Voltage	1.4	d-c volts
Current	0.05	amp.
Maximum Overall Length		4"
Maximum Seated Height		3-7/16"
Maximum Diameter		1-3/16"
Bulb		T-9
Base		Small Shell Octal 8-Pin
Pin 1 - No Connection		Pin 5 - Pentode Grid
Pin 2 - Filament +		Pin 6 - Diode Plate
Pin 3 - Pentode Plate		Pin 7 - Filament -
Pin 4 - Pentode Screen		Pin 8 - No Connection
Mounting Position	Any	



BOTTOM VIEW (G-7AM)

AMPLIFIER

Plate Voltage	110 max. volts
Screen Voltage	110 max. volts
Zero-Sig. Cathode Current (Pentode Unit)	6 max. ma.
<i>Typical Operation and Characteristics - Class A₁ Amplifier:</i>	
Plate	90 volts
Screen	90 volts
Grid	-4.5 volts
Peak A-F Grid Voltage	-4.9 volts
Zero-Signal Plate Cur.	3.4 ma.
Max.-Signal Plate Cur.	3.4 ma.
Zero-Signal Screen Cur.	0.7 ma.
Max.-Signal Screen Cur.	1.2 ma.
Plate Res. (Approx.)	0.3 megohm
Transconductance	800 μ mhos
Load Resistance	25000 ohms
Total Harmonic Distortion	7 %
Max.-Signal Power Output	100 mw

DIODE UNIT

The diode is located at the negative end of the filament, and is independent of the pentode unit except for the common filament.

July 1, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

TENTATIVE DATA